
# COANTEC



# Coantec C50 series Coantec Ultra HD Mega Pixel Industrial Videoscope



# SHENZHEN COANTEC AUTOMATION TECHNOLOGY CO.,LTD.

No.3, Crosslane 3, Yuanhu Road, Zhangbei, Ailian, Longgang District, Shenzhen, China, 518172
Tel: +86 -755-8972 8626 Fax: +86 -755-8978 6196







YouTube

Facebook

Coantec Website

# ✓ Excellent Performance

# **Software Features**

The new human-computer interaction interface, powerful software functions, and user-friendly and concise design make the inspection work more efficient.











Image real-time zoom

Real-time video capture

Video play fast forward and rewind

Image display color, black and white, negative film optional











Image file renaming and labeling

screen up and down flip

Video picture classification storage

# **Hardware Features**





### HD Image

HD display, miniature HD industrial camera, clear image, fexcellent image quality, effectively restore the true colors and better present internal details.

### Super Light

The rear-mounted optical fiber light quide lighting system, the maximum illuminance can reach to 100,000 Lx,the brightness can be adjusted according to the detection environment to obtain better observation results.

### Video Output

HDMI high-definition video output interface, connect the device with an external large screen, suitable for expert or multi-person consultation.

### Long-lasting Life Battery

The battery can work continuously for about 4 hours, and it is equipped with a set of backup batteries to support long-term inspection work.


### • Explosion-proof Certification

Certification of the Quality Supervision and Inspection Center for Low-Voltage Explosionproof Electrical Products in the Machinery Industry, Explosion-proof Mark Ex ic II B T4 Gc.

# **Excellent Quality**




- Double tungsten alloy braided insert tube of 4 layers
- IP67 protection level, waterproof and dustproof
- Stable and reliable laser welding process
- The camera adopts sapphire lens, which has high hardness, strong abrasion resistance, impact resistance, and the surface is not easily scratched.



The probe part adopts a laser welding process with more than 100 points, and each point is accurately welded in place in strict accordance with the standard, ensuring the reliability of the welding spot welding and the strength of the welding, and effectively guaranteeing the stability and reliability of the probe processing

and the overall product.



This diagram is not drawn in proportion, only for illustration.

# ✓ Easy Operation

# **Intelligent Navigation Menu**

- The navigation menu design is simple and clear, easy to understand and easy to use, novices can get started without training.
- Support ten languages: Simplified Chinese, Traditional Chinese, English, Japanese, Korean, German, French, Portuguese, Spanish, Russian.
- 0.1 second automatic exposure, automatic noise reduction, fast capture of the real details of the detected object, and feedback through high-definition pictures.





Photo / video button Ergonomic design-easy opration

Compact design, superior product performance, and easy-to-use operation with one hand, giving you an unprecedented ease of use.





# **Multi-function Electric Joystick**



- The unique rocker closed-loop control technology enhances the bending sensitivity and steering control of the probe for more precise operation.
- The electric joystick can control the probe to be guided in 360°all-way, with a strong sense of control, flexible steering and precise angle, and it has one-key lock, step-by-step fine adjustment, fast and slow adjustment, automatic reset, OK confirmation, menu navigation function, making inspection work easier.


# Lightweight and Portable





- One hand-held design, the whole machine (with battery) weighs only 1.35kgs, optional leather shoulder bag, safe and portable, Whether it's checking the fan gearbox on a 100-meter tower or a complex large machine, the C50 Industrial Videoscope is designed to make it easier to use.
- The instrument case adopts industrial grade anti-drop design, which is more compact and sturdy. It can be easily placed in the luggage racks such as airplanes, high-speed rails and trains during business trips.

# ✓ Strong Environmental Adaptability





Provide lifetime warranty service for rear-mounted LED light source to solve customers' worries.



# **Application Field**

It can be widely used in aerospace, special inspection industry, energy and power, automotive aftermarket, automobile manufacturing, shipbuilding, rail transit, petrochemical industry, food and drug machinery, mold casting, mechanical processing, construction engineering, police safety, military equipment, testing of municipal pipelines, university research institutes and many other fields.

# **Technical Specification**

Host		
Display Dimension	5-inch HD display	
Digital Zoom	Support real-time 4x zoom ,8x partial zoom when playback	
LED Brightness Leve	vel 0-7 level adjustment	
Auxiliary Measureme	ent Function Cross cursor guide	
Photo/Video	With photo and video functions, can be captured during recording	
Video Play	Video playback can fast forward and rewind	
Document Format	Image :JPEG/BMP; Video:MP4	
Image Rotation	0°/90°/180°/270°	
Image Preview Li	ist preview mode,full-screen viewing optional/delete/time watermarking/file rename/add note etc.	
Output Port	HDMI	
Storage Medium	Standard 8G capacity SD card, maximum support 32G	
Manu Languaga	Simplified Chinese、Traditional Chinese、English、Japanese, Korean,	
Menu Language	French, German, Portuguese, Spanish, Russian, Italian, Dutch etc.	
Protective Device	Buffer protection device for connecting host and wear-resistant tube	
Emergency Lighting	Glare LED emergency lighting	
System Security	Protect power-on password lock function	
Host Dimension	380mm*135mm*85mm	
Package Dimension	600mm*395mm*235mm	
Host Weight	1.45kg(standard 6020 tube)	

Host Weight	1.45kg(standard 6020 tube)			
Tube				
Probe Diameter (±0.1mm)	Ф3.9	Ф4.8	Ф6	Ф8
Tube Length	1-3m	1-3m	1-5m	1-10m
Tube Material	Tungsten alloy wire wear-resistant braided tube			
Camera Pixels	1,000,000			

Tube					
View Direction	Forward		Forward/Side	Forward/Side	Forward/Side
Depth of Field	5	-100mm	8-80mm (Standard) /7-150mm (Optional)		
Field of View		120°	110°/70°	110°/70°	110°/70°
Lighting Mode	Rear-	mounted LED, ptical fiber	Rear-mounted LED, optical fiber	Rear-mounted LED, optical fiber	Rear-mounted LED, optical fiber
Joystick Control	360° all-way articulation				
Probe Unidirectional Bending Angle		ng Angle	≥150°±10°		
Bending Lock	One-key lock				
Step Regulation	Step regulation between high-speed and low-speed bend				
Bending Control Mode Electric con		Electric cont	trol		
Probe Waterproof Level IP67		IP67			

Power		
Power Supply	Rechargeable lithium battery (with battery reverse protection)	
Battery	3.7V,3200mAh	
System Operating T	me	≥4H

Operation Environment	
Machine Operating Temperature	-10°C-50°C
Probe Operating Temperature	-20°C-60°C
Storage Temperature	-20°C-60°C
Relative Humidity	15%-90%

Configurations	5
Standard	C50 videoscope x1,instrument case x1,lithium battery x2sets, charger x1, card reader x1,
Configurations	8G SD card x1, user manualx1,precautions for use x1
Optional Configurations	Micro HDMI cable, Hand-held casing,High-grade instrument case (with insert tube storage tray), Pipe Centralizer

### Distributor

If the technical parameters are changed, please refer to the actual products, there will be no prior potice. All products

If the technical parameters are changed, please refer to the actual products, there will be no prior notice. All products are trademarks or registered trademarks of the owner of products.